


A E X T R A 2 0

OPEN YOUR STYLE



◆ CAESAR ◆
DESIGNED IN ITALY MADE IN USA



THICKNESS 3/4"

RANGE 24"x24"

Rectified_Squared



TITANIO



GEA



GRAUSTEIN



CLASSICO CONTRO



ROVERE



CINDER



24"x24" CLASSICO CONTRO



24"x24" CINDER

COLORED-BODY PORCELAIN TILES - RECTIFIED

Colored-body porcelain stoneware tiles are produced minimizing the color difference between the glaze and the body. Nevertheless, the design is visible only on the surface.

	24"x24"
Titanio	●
Gea	●
Graustein	●
Classico Contro	●
Rovere	●
Cinder	●

- Porcelain Stoneware
- Floor
- BOOT 3000 compliant
- Thickness 3/4"
- Rectified Tile
- NO V.O.C
- Frost Proof
- Low water absorption (<0,5%)
- Made in Usa

If the application of the 3/4" inch (20 mm) slabs foresees the ceramic product used in structural installations, the project engineer and/or customer must carefully assess the project requirements with regard to the technical specifications of the slabs. To prevent the risk of damage or injury, the manufacturer recommends:

- With regard to a raised floor installation a ceramic slab may fracture on impact if a heavy object falls on it from any significant height. Therefore the manufacturer recommends to check the specific intended use before starting the installation and to follow table for raised installation provided below. In certain conditions, reinforcing must be applied on the back of the slabs (double glass fibre net or a galvanized steel sheet) supplied and applied by the manufacturer;
- With reference to any dry installation system of flooring above the ground level, the manufacturer recommends to comply with local regulations and conditions of use with regard to wind-load, loadbearing, seismic events, etc. Failure to comply with these recommendations may lead to improper use of the product and could cause serious damage or injury.


INSTRUCTIONS FOR RAISED FLOOR INSTALLATION – USA – CANADA – OCEANIA		
	RAISE OF THE FOOT PLAN	
Size	Up to 3/4 inch	Above 3/4 inch
Size 24"x24" 	4 supports/slab (0,32 supports/sqf - 3,4 supports/mq)	Please contact Ceramiche Caesar (Caesartech dept.)

WARNING

Outdoor pavings installed unglued above the ground level are subject to the action of the wind, with the risk, in some cases, of becoming airborne. The manufacturer recommends to require the assistance of a qualified professional in order to check the suitability of the installation system above the ground adopted,
in accordance with the local laws and regulations and the conditions of use.
Failure to do so could result in serious injury or property damage.

A ceramic slab installed on a raised pedestal system may fracture on impact if a heavy object is dropped onto it from a height, with a risk of injury to anyone standing or walking on such slab.
Failure to adhere to the manufacturer's instructions for installation of slabs on raised pedestal systems may result in serious injury.

For further information and recommendations concerning the installation systems please refer to www.caesarceramicsusa.com website.



A E X T R A 2 0
OPEN YOUR STYLE

◆ **CAESAR** ◆
DESIGNED IN ITALY MADE IN USA
www.caesarceramicsusa.com

CAESAR CERAMICS USA, INC.

35 James Way - Eatontown, NJ 07724
Phone: +1 (732) 389 5757
fax: +1 (732) 389 8589

PORCELAIN STONEWARE

Color reproductions may vary from actual products.

Caesar reserves the right to modify the products illustrated in this catalogue for reasons of production or to improve quality. Samples are purely indicative. Packaging and weights may vary for production reasons. Contact our sales department when ordering.

Caesar warrants that our products meet or exceed the requirements of ANSI, specification ANSI A137.1: 2012, as shown in our Tile Performance Data sheets.

The Caesar complete terms and conditions of sale (including limited warranty) are specified in the price list. Should you need further information, please contact our sales department.

